

Optimo Style 25-250

4th Generation 10X Zoom

specifications

Zoom ratio 10x

Focal Length 25 - 250 mm

Aperture f/3.2 - T3.5 with no ramping

Close Focus 4 ft – 1.22 m

Internal Focus Yes

Image coverage S35+: 31.4 mm diagonal

Weight (approx.) 16 lbs – 7.3 kg Length 377.4 mm Front diameter 136 mm

Available accessories







Extenders or Format Adapters 1.4x & 2x



Front Protective Glass



MAIN FEATURES

- 4th generation 25-250mm, the signature focal range that has served the motion picture industry for the past 50 years
- Totally re-engineered optics & mechanics, with internal focus/zoom mechanism
- Constant T-stop of 3.5 throughout the entire zoom range
- Color reproduction matches the highly acclaimed OPTIMO lens series
- Internal focus, internal zoom, constant lens volume
- Extremely well controlled distorsion and breathing
- Close focus of 4 ft 1.22 m enables extreme close-up shots
- Built-in lens encoder provides lens metadata (focus, zoom, T-stop) via industry standard Cooke's / E protocol
- Lens data can be displayed on camera monitors to assist critical focusing, and be recorded in camera to support VFX / post production work.

 Please click here to download the latest version of your lens Software and the process to do it
- Internal filter slot allows use of standard screw-in filters (M40.5mm supplied, M46mm optional) for creative image control
- Front thread for optional protective glass
- Compatible with Optimo 1.4x and 2x extenders: 35 350 mm T4.9 (with 1.4x) and 50 500 mm T7 (with 2x)
- Both focus and zoom elements are guided through an internal mechanical rod system, which helps maintain optical quality even after rough handling / transportation
- Adapted to extreme production environments (passive athermalisation from -20°C to +40°C)
- PL mount lens. Easily interchangeable to PV or Canon EF mounts
- Interchangeable focus scale ring from feet to meters

Field of view for 22x16 mm

Focal Length	25 mm	250 mm
Horizontal angular field of view	47.6°	5°
Object dimensions at MOD (mm)	789x565	78.9x58.1

