sachtler





The Dutch Head 35 also features Sachtler's patented fluid damping and counterbalance systems. In addition, it has a cross-sliding plate that uses a high precision dove-tailed guidance with a sliding range of 60 mm / 2.4". This enables the camera's center of gravity to be aligned exactly over the head's swiveling axis. The head is able to tilt the horizon, and features a scale on the right side panel that shows the exact degree of third axis movement.

Technical Facts

Recommended for

Weight

Payload

Sliding range - plate

Counterbalance

Grades of drag

Tilt range

Temperature range

Camera fitting

Pan bar(s)

Payload

C.O.G.* min. kg/max. 75 / 3" 0 / 0 67.6 / 100 / 4" 0 / 0 58.4 / 125 / 5" 0 / 0 51.5 / 150 / 6" 0 / 0 46.0 / 175 / 7" 0 / 0 41.6 / 200 / 8" 0 / 0 37.9 / 250 / 0/0 32.3 / 300 / 0/0 28.1 /

Fluid heads with Touch & Go plate 35

6 kg / 13.23 lbs

up to 50 kg / 110.2 lbs

60 mm / 2.4 in

in 7 steps


7 diagonal + 0


±60°

-40° to +60° C / -40 to +140° F


Touch & Go Plate 35

1, telescopic, Type Plus





Damping



Dimensions

Further photos





Order data

Article	Order code
Dutch Head 35 Fluid head	3004

This product is also available in the following systems:

Article Order code

Accessories